

ARAKNO WALL - TELESCOPIC WALL MOUNT FOR VIDEOP. BLACK

SKU: 15462



Net weight	8 kg
Closed Length	320x200x700mm
MAX LOAD	45 kg
Mount Rotates	360°
Tilt angle	+/- 25°
Material	Fe (structure)
Treatments	powder-coated black/white

Categories: [Arakno](#), [UFO Video Projector Wall Mount](#), [Video Projector Mounts](#)

An adjustable wall-support for videoprojectors, ideal for mounting high-end and heavy projectors. It is both easily and quickly installable. The “Arakno” regulation system allows for precise, fast and dependable focusing of projected images.

N.B. Arakno is not included.

Also available in:

- [White \(Cod: 15463\)](#)

[QUOTATION REQUEST](#)

x

REQUEST A QUOTATION

Name *

Surname *

Company *

Email *

Message

☐ I have read and accept the Privacy Policy (*)

[Read our Privacy Policy](#)

Send

x

GALLERY

Intertek

VERIFICATION
of conformity with European Directives

Job No:

4126

Type of equipment:

Wall mounted LCD support

Applicant / importer:

Euromet S.r.l.
Zona Industriale Ronchini
60025 Loreto (AN) - Italy

Manufacturer / importer:

(same as applicant)

Type designation:

Arakno

Rating:

Arakno: Max load supported 45 Kg

Standards used for showing compliance with the essential requirements in the specified directive(s):

Standard(s)	Test report(s)	Issued by	Control
EN 60065: 2002 Cl. 19-6	1066001UCI-003	Intertek Italia s.r.l.	January 16, 2009

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified EU Directive(s). After preparation of the necessary technical documentation as well as the conformity declaration the CE marking can be affixed on the equipment. Other relevant Directives have to be observed.

Complimentary, January 16, 2009

Arakno Fagar

Operations Manager

INTERTEK ITALIA s.r.l.

via Principe di Ussita, 114 - Campotomido (UD), Italy

Tel: +39 0432 653411 - Fax: +39 0432 653499 - www.intertek-italiano.com



Easily adjustable lateral handle for regulating the boom length.
Manopola laterale per una facile ed affidabile regolazione telescopica.

